

# Foam Cleaning Equipment PumpSet Freq. 38-210T IE5

High Pressure. TANK Supply

Item no.: 89918



PumpSet Freq. 38bar 210L/min. Transmitter. TANK supply.

## Purpose and use

The Frequency controlled PumpSet Freq. 38-210T IE5 is powerful and designed for easy use and service. It is floor mounted and is for sites that require cleaning by high pressure.

Basically it is very simple to use. When there is a demand for water, it automatically starts activated by Transmitter / Grundfos Stop Function. When there is no more need for water, it automatically stops.

It is built for supplying pressure boosted water to Injectors, Aut.Satellites and other cleaning equipment.

## Features / benefits

- |                        |  |
|------------------------|--|
| Functions:             | Frequency controlled automatic booster pump for high pressure cleaning etc. in harsh environment   |
| Operator friendly:     | Easy understanding of the functions<br>LED indicators for status and Alarm   |
| Automatically control: | Starts automatically on demand for water. It stops slowly (~30 sec) when there is no need for water.<br>Motor and pump is over heat protected. |
| Options:               | Grundfos GO App MI301 / M201 for SetUp.  |

PS Freq. IE5  
38-210T





## General Description

The Frequency controlled PumpSet Freq. 38-210T IE5 is built to boost the water pressure for foam cleaning equipment such as Injectors etc. The system is made mostly of stainless steel so it is robust against harsh environments.

As standard a non-return valve is mounted in the water outlet to secure the pump and the water supply system against pressure shocks. A filter is mounted in the water Inlet.

The control system automatically starts the pump when there is a demand for water. The frequency control system makes the pump go from OFF to full load in 3 seconds. When there is no need for water it automatically stops slowly. This way of start-up and slow down makes it more comfortable for the cleaning operator. Besides that it avoids high current shock in the power supply system.

The unit is programmable by the optional remote control MI301 / M201 and an App on an Android or iOS smartphone.

## Placing Orders and Enquiries

Correspondence concerning new orders or progressing existing orders, contact: Mr. Anders S. Christensen

## Technical enquiries

Enquiries relating to product performance should be directed to:

Mr. Aksel A. Utoft  
Mr. Anders S. Christensen

ScanFoam® Cleaning Equipment ApS.  
Niels Bohrs Vej 29b, Stilling  
8660 Skanderborg  
Denmark

Telephone: +45 86 57 25 99  
Fax: +45 86 57 20 86  
E-mail: anders.christensen@scanfoam.com  
order@scanfoam.com

## Specifications

Working area:	Pressure boost range min/max:	30 -> 38 bar
	Flow max at 35 bar boost.	210 l/min
	No. of users flushing 23-25L/min.	7-8
Water inlet:	Connection:	2" BSP (Female)
Limitation:	Min. feed pressure	2 bar
	Max. feed pressure	8 bar
	Max. temperature	70 °C
NOTE!	When using HOT water be aware of the NPSH. Place the tank high. Preferably > 3 meter above the PumpSet	
Power supply	3x400 VAC 50Hz	
	Power consumption max.	2X 7,5 kW
	Backup fuse size Aut./T. Max.	2X 32 Amp
	<i>Re. dimensioning, always use the local rules.</i>	
Weight:		~225 kg
Alarm:	Motor over heated; phase drop out Pump temperature overheat	
Information:	Red and green LED	Alarm, Standby, Running
Includes	Built in double safety:	2X Non-Return Valves

## Options:

86348	Level Switch for shutting down pump when low water level I tank
Stand:	Feet for floor standing.
PLC control	The PumpSet has several options for remote control. E.g. variable pressure setting etc.
MI301 / M201	Hand held remote programming and reporting unit by the Grundfos GO App.

## NOTE! FOR TRANSMITTER CONTROL / GRUNDFOS STOP-FUNC.

The outlet tube system must be tight. Leakage must not exceed 1% pressure loss in a period of 10 minutes.

