

Foam Cleaning Equipment

Mobile Cleaning Unit M60a. **IE5**

Medium Pressure

Item no.: 96011



25-60 Q
IE5

Purpose and use.

The Mobile Cleaning Unit M60a IE5 is compact and designed for easy use and service. It is for sites that require cleaning by Flushing, Foaming and Disinfection.

It is capable of producing dry dense foam and by adjusting the air pressure, more wet dense foam.

The Mobile Cleaning Unit M60a is manually operated by a valve which is easy to operate. The compressor automatically shuts off when flushing. All materials that are in contact with the product are all corrosion resistant.

Features / benefits.

Functions:	Cleaning with Flush / Foam / Disinfection
Operator friendly:	Easy understanding of the functions
Variable foam density:	Capable of producing dry dense foam Capable of producing wet dense foam
Adjusting product conc.:	Easy change of concentration by changing the colour coded orifice nozzle
Few installation requirements:	Only water and electricity required.



General Description

The Mobile Cleaning Unit M60a. IE5 is a mobile Frequency controlled PumpSet and an Injector build into one cabinet. It is made mostly of stainless steel so it is robust against harsh environments. As standard is has a non-return valve mounted at the water inlet which avoids pressure chocks in the water supply. The compressor automatically shuts off when flushing is performed.

The wheels used, is made of rubber that do not give marks on the floor.

The control automatically starts the pump on demand for water. Automatically it stops slowly when there is no need for water. The pump motor is frequency controlled and by default programmed to perform 100%. Programmable between 50-100%.

Placing Orders and Enquiries:

All orders will be acknowledged by fax, unless other special arrangements have been made.

All correspondence concerning new orders or progressing existing orders, should be directed to:

Mr. Anders S. Christensen

Technical enquiries:

Enquiries relating to product performance should be directed to:

Mr. Aksel A. Utoft

Mr. Anders S. Christensen

ScanFoam® Cleaning Equipment ApS.

Niels Bohrs Vej 29b, Stilling

8660 Skanderborg

Denmark

Telephone: +45 86 57 25 99

Fax: +45 86 57 20 86

E-mail: ac@scanfoam.com

order@scanfoam.com

Specifikations

Water Inlet:

Connection: Quick Coupling w. nipple for 3/4" hose

Limitation:

Min. feed pressure	2 bar
Max. feed pressure	10 bar
Max. temperature	60 °C

Water consumption at 25 bar & 10 m 1/2" hose:

Flushing nominal 1 user	30 l/min
Flushing nominal 2 users	60 l/min
Flushing max.	70 l/min
Foaming	8 l/min

Power supply

Volt	3x400 VAC
Max.	4,0 kW
Backup fuse max:	16 Amp

Always follow local rules when installing the equipment
EU Compliance / Energy efficiency **IE5**

Prod. inlet:

Connection:	1 suction tube
Dosing range	1-6%

Outlet:

Connection:	1/2" quick coupling
Recommended max. length 1/2" hose	10 meter

Weight net: 116 kg

Size:	Raw shipping measures (LxWxH)	130 / 61 / 55 cm
	Full operational measures (LxWxH)	150 / 65 / 100 cm

Included accessories:

15m el. wire. Quick coupling for inlet hose. Suction tube.

Options:

- > 85590. Valve set for 2 chemicals
- > 85720. Double Outlet for flushing. See picture in small frame
- > 83380. Accessories for Sat Mobile Hose, Ball valve, Set of nozzles
- > 81139. Hose LP Red 3/4" Inlet. Ask for length

