








Item	Technical Data	Description
<p>Discharge low pressure hose 1/2".</p> <p>Item No:</p> <p>80176 10 m</p> <p>80177 15 m</p> <p>80178 20 m</p> <p>80179 25 m</p> <p>80180 30 m</p> <p>80181 35 m</p> <p>80219 40 m</p> <p>80215 50 m</p>	<p>Max. pressure/temp. 50 bar/23°C. 25 bar/70°C.</p> <p>Other length on request</p> <p>½" BSP female</p> <p>Fittings made of chromed steel</p>	<p>Standard Female connection</p> <p>Discharge low pressure hose 1/2", with inside thread chromed connections.</p> <p>Any length on request</p>
		
<p>Low pressure hose 1/2" connect. Stainless Steel</p> <p>Item No:</p> <p>84714 10 m</p> <p>80198 15 m</p> <p>80184 20 m</p> <p>84695 25 m</p> <p>80185 30 m</p>	<p>Max. pressure/temp. 50 bar/23°C. 25 bar/70°C.</p> <p>Other length on request.</p> <p>½" BSP female</p> <p>Fittings made of Stainless Steel</p>	<p>Standard Female connection</p> <p>Discharge low pressure hose 1/2", with inside thread stainless steel connections.</p> <p>Any length on request</p>
		
<p>LP hose ½" Outside thread</p> <p>Item No:</p> <p>85410 10 m</p> <p>85415 15 m</p> <p>85420 20 m</p> <p>85425 25 m</p> <p>85430 30 m</p> <p>85431 35 m</p>	<p>Max. pressure/temp. 50 bar/23°C. 25 bar/70°C.</p> <p>Fitting material: Chromed steel.</p>	<p>Low pressure hose for cleaning products.</p> <p>Suitable for competitive Equipment.</p> <p>Also available with Stainless Steel connections</p> <p>Any length on request</p>
		

Item	Technical Data	Description
<p>Discharge high pressure hose 1/2"</p> <p>Item No:</p> <p>80186 10 m</p> <p>80187 15 m</p> <p>80188 20 m</p> <p>80189 25 m</p> <p>80190 30 m</p> <p>80191 35 m</p> 	<p>Max. pressure/temp. 210 bar/150°C.</p> <p>Other lengths and connections on request.</p> <p>Stainless Steel fittings available</p>	<p>Female connection</p> <p>Discharge high pressure hose 1/2", with inside thread chromed connections.</p>
<p>Discharge low pressure hose 1/2".</p> <p>Item No. 85138</p> 	<p>Hose "Low Pressure"</p> <p>Max. pressure/temp</p> <p>- 50 bar / 23°C.</p> <p>- 25 bar / 70°C.</p>	<p>Length:</p> <p>- 120 m</p>
<p>Chemical hoses ø6, ø8 and ø10 hoses PTFE/Stainless Steel</p> <p>Eks with 1/4" outside thread connection</p> <p>Item No:</p> <p>84506 0,30 m</p> <p>89447 0,51 m</p> <p>89448 1,0 m</p> <p>89418 2,0 m</p> <p>89445 5,0 m</p>  <p>Example: Length=0,51m</p> <p>Union connection</p> <p>Picture of hose ø8 and 1/4" connection</p>	<p>Available connections:</p> <p>1/8" male and 1/8" female Hose inner dia: 6mm</p> <p>1/4" male and 1/4" female Hose inner dia: 6/8/10mm</p> <p>3/8" male and 3/8" female Hose inner dia: 6/8/10mm</p> <p>Max pressure 50 bar</p> <p>Max temperature 100 °C</p> <p>Sample picture</p>  <p>3/8" Male</p> <p>Union connect</p> <p>Picture of hose ø6 and 3/8" with union connection</p>	<p>The hose series is made for concentrated chemicals except strong Chlorine.</p> <p>Inner hose: Teflon / PTFE.</p> <p>Fittings in touch with media: AISI 316</p> <p>Hose protection: Flexible net made of Stainless Steel AISI 304.</p> <p>Simple male or union connection is available</p> <p>Any length on request</p>