

Foam Cleaning Equipment
Cleaning Unit M11 / S11
Medium Pressure
Item no.: 84520 / 85640



11-35

Purpose and use.

The unit is produced in 2 versions. The mobile unit M11 with 4 wheels and the stationary unit S11 for wall mounting.

The Cleaning Unit M11a / S11a are compact and designed for easy use and service. It is for sites that require cleaning by Foaming and Disinfection.

It is capable of producing dry dense foam and by adjusting the air pressure, more wet dense foam.

The Mobile Cleaning Unit M55a is manually operated by a valve, which is easy to operate. The compressor automatically shuts off when flushing. All materials that are in contact with the product are all corrosion resistant.

Features / benefits.

Functions:	Cleaning with Flush / Foam / Disinfection
Operator friendly:	Easy understanding of the functions
Variable foam density:	Capable of producing dry dense foam Capable of producing wet dense foam
Adjusting product conc.:	Easy change of concentration by changing the colour coded orifice nozzle
Few installation requirements:	Only water and electricity required.



General Description

The Cleaning Unit M11 / S11 is a PumpSet and an Injector build into one cabinet. It is made mostly of stainless steel so it is robust against harsh environments. As standard is mounted a non-return valve to avoid pressure chocks in the water supply. The compressor automatically shuts off when flushing.

The wheels used, is made of rubber that do not give marks on the floor.

The control automatically starts the pump on demand for water. It stops after 5-60 sec. (Default: 12 sec.) when there is no need for water.

Placing Orders and Enquiries:

All orders will be acknowledged by fax, unless other special arrangements have been made.

All correspondence concerning new orders or progressing existing orders, should be directed to:

Mr. Anders S. Christensen

Technical enquiries:

Enquiries relating to product performance should be directed to:

Mr. Aksel A. Utoft

Mr. Anders S. Christensen

ScanFoam® Cleaning Equipment ApS.
Niels Bohrs Vej 29b, Stilling
8660 Skanderborg
Denmark

Telephone: +45 86 57 25 99
Fax: +45 86 57 20 86
E-mail: anders.christensen@scanfoam.com
order@scanfoam.com

Specifikations

Water inlet:

Connection: M11: Quick Coupling for 3/4" hose / S11: 1/2" BSP

Limitation:

Min. / Max. feed pressure	2 / 5 bar
Max. temperature	50 °C
Pressure boost	12 bar

Water consumption at 25 bar & 10 m 1/2" hose:

Flushing nom.	30 l/min
Flushing max.	50 l/min
Foaming	7 l/min

Power supply

Volt	1x230 VAC
Max.	2,5 kW

Prod. inlet:

Connection:	1 suction tube
Dosing range	1-6%

Outlet:

Connection:	1/2" hose nipple
Recommended max. length 1/2" hose	10 meter

Weight:

65 kg

Size:

Raw shipping measures (LxWxH)	70 / 55 / 120 cm
Full operational measures (LxWxH)	85 / 55 / 115 cm

Included accessories:

M11: 15m el. Wire with CE plug. Both units: Suction tube and orifice nozzles. Ask for further information.

Optional equipment:

- Set of accessories. Item no: 83380. See picture.
- Plug Schuko 230V CEE 7/7Sh. (Most EU countries)
- Armed electrical wire
- Inlet hose. Example: 81154. Length up to 20m



Product Inlet
Water Inlet
Power: 230 VAC
Outlet

