


Foam Cleaning Equipment Injector Mobile MP 10-50

Medium Pressure

Item no.: 88056



ScanFoam®



10-50 Bar

Purpose and use.

The Injector Mobile MP consists of an injector, mounted on a trolley. The design is compact and for easy use and service. It is for sites that require cleaning by Foaming and Disinfection. The trolley is made in stainless steel and has room for hose, accessories etc.

The injector is capable of producing dry dense foam and by adjusting the air pressure, more wet dense foam.

The Injector Mobile MP is manual operated by valves, which is easy to operate. All materials that is in contact with the product, is corrosion resistant.

Features / benefits.

Functions:	Cleaning with Flush / Foam / Disinfection
Operator friendly:	Easy understanding of the functions
Variable foam density:	Capable of producing dry dense foam Capable of producing wet dense foam
Adjusting product conc.:	Easy change of concentration by changing the colour coded orifice nozzle
Few installation requirements:	No electricity required



General Description

The Injector works like a hydraulic foam cabinet, (the Injector is essentially a “static pump”). Injectors work on the principle of a pressure differential: A vacuum is created which pulls “or pumps” the product into the mixing chamber. As standard, a non-return valve in the water inlet is mounted.

The trolley has mounted wheels without rubbing off affect. Furthermore, an outlet hose and a set of tubes are included.

Ordering Information

Shipping: All correspondence concerning shipping, should be directed: Mrs. Lene Wittendorf

Placing Orders and Enquiries:

All orders are acknowledged by fax, unless other special arrangements have been made.

All correspondence concerning new orders or progressing existing orders, should be directed to:

Mr. Anders S. Christensen

Mrs. Lene Wittendorf

Technical enquiries:

Enquiries relating to product performance should be directed to:

Mr. Aksel A. Utoft

Mr. Anders S. Christensen

ScanFoam[®] Cleaning Equipment ApS.

Niels Bohrs Vej 29b, Stilling

8660 Skanderborg

Denmark

Telephone: +45 86 57 25 99

Fax: +45 86 57 20 86

E-mail: anders.christensen@scanfoam.com

lene.wittendorf@scanfoam.com

Specifications

Water inlet:	Connection:	1/2" BSP (Female)
Limitation:	Min. feed pressure	10 bar
	Max. feed pressure	50 bar
	Max. temperature	70 °C

Water consumption at 25 bar & 10 m 1/2" hose:		
	Flushing nominal	30 l/min
	Flushing max.:	60 l/min
	Foaming	10 l/min
	Disinfecting	13 l/min

Air inlet:	Connection	1/4" BSP Female
Limitation:	Min. feed pressure	6 bar
	Max. feed pressure	10 bar
Air consumption at 6 bar		150 l/min

Prod. inlet:	Connection:	1 suction tube
	Dosing range	1-6%

Outlet:	Connection:	1/2" quick coupling
	Length of included hose 1/2"	10 meter
	Max length hose recommended	25 meter

Weight:	22 kg
---------	-------

Included accessories:
Hose 1/2" 10 meter with ball valve, Foam tube, Disinf. tube, Flushing tube. Brackets for the hose and the accessories.

