

Item

Technical Data

Description

## 8. Hose reels

**Hose reel. Automatic**  
Item No. 81810




Size:  
Ø550 mm  
W320 mm

Optional accessory for both  
hose reels:  
Pivoting wall bracket: 86476

Hose reel for max. **20 m.** 1/2" hose.  
The Reel is manufactured from high corrosion resistant material.  
The outlet has step less adjustment and the Reel is equipped with a safety catch that locks the drum when changing hose or swivel.

**Hose reel. Automatic**  
Item No.81811



Hose reel for max. **25 m.** 1/2" hose.

**Hose reel. Aut.**  
Item No. 82128



Dimensions:  
Inlet 1/2" BSP Male  
Outlet 1/2" BSP Male  
Diameter ø510 mm  
Max pressure at 100°C:  
Standard 25 bar  
*100 bar and 200 bar available on request*

**Note!:** The performance can be limited by the max temperature or pressure of the hose.

Automatic hose reel in stainless steel.  
Max. **20 m.** 1/2" (ø22) hose.

Price does not Incl. a hose.

The reliable construction provides maintenance-free operation for safe and easy use.

**Mounting: Wall, underneath roof and on the floor.**

The hose handle rollers can be adjusted so that the hose goes vertically or horizontally from the reel. Default is horizontally.

Material: Stainless Steel.






**Pivoting bracket**  
Item No. 86173

Material Stainless Steel



The pivoting bracket pivots +/- 40° from side to side.

It includes bolts for mounting the hose reel 82128. See above.

Item	Technical Data	Description
<p><b>Hose reel Aut.</b> Item No. 82145</p> 	<p>Hose reel in <b>stainless steel</b> for <b>up to. 30 m. 1/2" hose.</b></p> <p>Dimensions:            Inlet            1/2" BSP female            Outlet           1/2" BSP female            Diameter:        ø510 mm</p> <p>Max pressure at 100°C:            Standard        25 bar  <i>100 bar and 150 bar available on request</i></p> <p><b>Note!:</b> The performance can be limited by the max temperature or pressure of the hose.</p> <p>Hose length:            ø22 // 1/2"        Max 30m            ø28 // 3/4"        Max 22m            ø34 // 1"            Max 17m</p>	<p>The hose reel is for mounting on: Wall and Ceiling</p>  <p>The hose guide is adjustable for hose forward, hose downwards or whatever you can imagine except horizontal (flat) position.</p> <p>The reliable construction provides maintenance-free operation for safe and easy use.</p>
<p>Option for 82145: <b>Pivoting bracket</b> Item no. 83471</p> 	<p>Material <b>Stainless Steel</b></p>	
<p><b>Hose reel Aut.</b> Item No. 83470</p> 	<p>Hose reel in <b>stainless steel</b> for <b>up to. 50 m. 1/2" hose.</b></p> <p>Dimensions:            Inlet            1/2" BSP female            Outlet           1/2" BSP female            Diameter:        ø510 mm</p> <p>Max pressure at 100°C:            Standard        25 bar  <i>100 bar and 150 bar available on request</i></p> <p>Foot print (WxH)    49 x 35 cm</p> <p>Hose length:            ø22 // 1/2"        Max 50m            ø28 // 3/4"        Max 35m</p>	<p>The hose reel is for mounting on: Wall and Ceiling</p>  <p>The hose guide is adjustable for hose forward, hose downwards or whatever you can imagine except horizontal (flat) position.</p> <p>The reliable construction provides maintenance-free operation for safe and easy use.</p> <p>Pivoting bracket is not available for this hose reel.</p>

